

屋内照明器具特性	
品番 (品名)	XLX450CHVP
光源	LED3500_85_4600 x1 4600.0lm
管理番号	K0132113(6)DB1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	51	38	30	24	49	37	29	24	45	34	28	23	41	32	26	22	19	
		0.8	60	48	39	33	57	46	38	32	53	43	36	31	48	40	34	30	26	
		1.0	66	55	46	40	63	53	45	39	58	49	42	37	53	46	40	35	31	
		1.25	72	61	53	47	69	59	51	45	63	55	48	43	58	51	46	41	36	
下方投影面積	cm <sup>2</sup>	1.5	76	66	58	52	73	64	56	51	67	59	53	48	62	55	50	46	40	
		2.0	82	73	66	60	79	71	64	58	72	66	60	55	67	61	57	53	47	
取付高さ	器具間隔最大限		2.5	86	78	71	66	82	75	69	64	76	70	65	61	70	65	61	57	51
	横方向 (A)	縦方向 (B)	3.0	88	81	75	70	85	79	73	68	78	73	69	65	73	68	65	61	55
1.5m	1.98m	2.16m	4.0	92	86	81	76	88	83	78	74	82	78	74	70	76	73	69	66	60
2	2.61	2.71	5.0	94	89	85	81	90	86	82	78	84	81	77	74	78	75	72	70	63
2.5	3.24	3.3	7.0	96	93	89	86	93	90	86	83	87	84	81	79	81	79	76	74	67
3	3.87	3.89	10.0	99	96	93	90	95	93	90	88	89	87	85	83	83	82	80	78	71

