

# 屋内照明器具特性

品番 (品名)	LGB81811															
光源	LED3500_70_1950 x1 1950.0lm															
管理番号	K0142374(0)DR1															
BZ分類	BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	50%	室指数	照明率 ( X0.01)																ZCM		
下方光束	50%																				
保守率	良 中 否	0.67	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11	
		0.63	0.8	56	45	37	32	52	42	35	30	43	36	30	26	36	30	25	22	16	
		0.56	1.0	62	52	44	38	57	48	41	36	48	41	35	31	40	34	30	26	19	
			1.25	68	58	50	45	62	54	47	42	52	46	41	36	43	38	34	31	22	
下方投影面積	c m <sup>2</sup>	1.5	72	63	55	50	66	58	52	47	56	49	44	40	46	41	37	34	24		
		2.0	77	69	63	57	71	64	59	54	60	55	50	46	50	46	42	39	28		
取付高さ	器具間隔最大限		2.5	81	74	68	63	74	68	63	59	63	58	54	51	52	49	46	43	31	
	横方向 (A)	縦方向 (B)	3.0	83	77	72	67	77	71	67	63	65	61	57	54	54	51	48	46	33	
1.5m	1.25m	2.08m	4.0	86	81	77	73	80	75	71	68	68	64	61	59	56	54	52	49	36	
2	1.67	2.7	5.0	88	84	80	77	82	78	75	71	69	67	64	62	58	56	54	52	38	
2.5	2.08	3.33	7.0	90	87	84	81	84	81	78	76	72	69	67	65	60	58	57	55	40	
3	2.5	3.96	10.0	92	90	88	85	86	84	82	80	73	72	70	69	62	60	59	58	42	

