

屋内照明器具特性

品番 (品名)	LGB87012F															
光源	LDA4L-H-E17/S/4 ×1 440.0 1m															
管理番号	K0122401(2)DB1															
BZ分類	BZ4/0.9/BZ3															

器具効率	60%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	12% 48%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	3.4	2.7	2.3	2.0	3.3	2.6	2.2	1.9	3.0	2.5	2.1	1.9	2.8	2.3	2.0	1.8	1.6		
		0.8	4.0	3.4	3.0	2.7	3.9	3.3	2.9	2.6	3.6	3.1	2.8	2.5	3.3	2.9	2.6	2.4	2.2		
		1.0	4.4	3.9	3.4	3.1	4.3	3.7	3.4	3.1	3.9	3.5	3.2	2.9	3.7	3.3	3.0	2.8	2.6		
		1.25	4.8	4.3	3.9	3.6	4.6	4.1	3.8	3.5	4.3	3.9	3.6	3.4	3.9	3.6	3.4	3.2	2.9		
下方投影面積 等価発光面積	c m ²	1.5	5.0	4.5	4.2	3.9	4.8	4.4	4.1	3.8	4.5	4.1	3.9	3.6	4.1	3.9	3.7	3.5	3.2		
		2.0	5.3	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.7	4.5	4.2	4.1	4.4	4.2	4.0	3.9	3.5		
取付 高さ	器具間隔最大限		2.5	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	4.9	4.7	4.5	4.3	4.6	4.4	4.2	4.1	3.7	
	横方向 (A) H m	縦方向 (B) H m	3.0	5.6	5.3	5.1	4.9	5.4	5.2	5.0	4.8	5.0	4.9	4.7	4.5	4.7	4.5	4.4	4.3	3.9	
			4.0	5.8	5.6	5.4	5.2	5.6	5.4	5.2	5.1	5.2	5.0	4.9	4.8	4.8	4.7	4.6	4.5	4.1	
			5.0	5.9	5.7	5.5	5.4	5.7	5.5	5.4	5.2	5.3	5.2	5.1	4.9	4.9	4.8	4.7	4.7	4.2	
			7.0	6.0	5.9	5.7	5.6	5.8	5.7	5.6	5.5	5.4	5.3	5.2	5.1	5.0	5.0	4.9	4.8	4.4	
			10.0	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.6	5.5	5.4	5.4	5.3	5.1	5.1	5.0	5.0	4.5	

