

屋内照明器具特性	
品番 (品名)	LGB87077K
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0175930(0)DR1
BZ分類	BZ9

器具効率	68%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	33%	床	10%				10%				10%				10%				0%	
下方光束	35%		10%				10%				10%				10%				0%	
室指数		照明率 ( X0.01 )																ZCM		
保守率	良	0.63	0.6	3.0	2.1	1.6	1.2	2.7	1.9	1.4	1.1	2.2	1.6	1.2	9	1.8	1.3	9	7	4
	中	0.6	0.8	3.5	2.7	2.1	1.7	3.2	2.4	1.9	1.5	2.6	2.0	1.6	1.3	2.1	1.6	1.3	1.0	6
	否	0.56	1.0	3.9	3.1	2.5	2.0	3.6	2.8	2.3	1.9	2.9	2.3	1.9	1.6	2.3	1.9	1.5	1.3	7
			1.25	4.3	3.5	2.9	2.5	3.9	3.2	2.7	2.3	3.2	2.7	2.3	1.9	2.6	2.2	1.8	1.6	9
下方投影面積	cm <sup>2</sup>	1.5	4.5	3.8	3.3	2.8	4.2	3.5	3.0	2.6	3.4	2.9	2.5	2.2	2.8	2.4	2.1	1.8	1.1	
等価発光面積	cm <sup>2</sup>	2.0	4.9	4.3	3.8	3.3	4.5	4.0	3.5	3.1	3.7	3.3	2.9	2.6	3.0	2.7	2.4	2.1	1.4	
取付高さ	器具間隔最大限		2.5	5.2	4.6	4.1	3.7	4.8	4.3	3.8	3.5	4.0	3.6	3.2	2.9	3.2	2.9	2.7	2.4	1.6
	横方向 (A)	縦方向 (B)	3.0	5.4	4.9	4.4	4.0	4.9	4.5	4.1	3.7	4.1	3.8	3.5	3.2	3.4	3.1	2.9	2.6	1.8
Hm	1.59Hm	2.17Hm	4.0	5.6	5.2	4.8	4.5	5.2	4.8	4.5	4.2	4.4	4.1	3.8	3.5	3.6	3.3	3.1	2.0	
			5.0	5.8	5.4	5.1	4.8	5.3	5.0	4.7	4.4	4.5	4.2	4.0	3.8	3.7	3.5	3.3	2.2	
			7.0	6.0	5.7	5.4	5.2	5.5	5.3	5.0	4.8	4.7	4.5	4.3	4.1	3.9	3.7	3.6	2.4	
			10.0	6.1	5.9	5.7	5.5	5.7	5.5	5.3	5.1	4.8	4.7	4.5	4.4	4.0	3.9	3.8	2.6	

