

屋内照明器具特性	
品番 (品名)	L G B C 5 5 0 1 1
光源	LED3500_70_776 ×1 776.0 l m
管理番号	K0172982 (0) DR 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 7	4 5	3 8	3 2	5 6	4 5	3 7	3 2	5 4	4 4	3 7	3 2	5 1	4 3	3 6	3 2	3 0
			0 . 6 3	0 . 8	6 7	5 6	4 8	4 3	6 6	5 5	4 8	4 2	6 3	5 4	4 7	4 2	6 0	5 2	4 6	4 2	4 0
			0 . 5 6	1 . 0	7 4	6 3	5 6	5 0	7 2	6 2	5 5	5 0	6 9	6 1	5 4	4 9	6 6	5 9	5 3	4 9	4 7
				1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 7	7 5	6 7	6 1	5 6	7 2	6 5	6 0	5 6	5 4
下方投影面積 等価発光面積		c m ²		1 . 5	8 4	7 5	6 8	6 3	8 2	7 4	6 8	6 2	7 9	7 2	6 6	6 2	7 6	7 0	6 5	6 1	5 9
				2 . 0	8 9	8 2	7 6	7 1	8 8	8 1	7 5	7 0	8 4	7 9	7 4	7 0	8 1	7 7	7 2	6 9	6 6
				2 . 5	9 3	8 6	8 1	7 6	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 1
取付 高さ	器具間隔最大限			3 . 0	9 5	9 0	8 5	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 7	8 4	8 1	7 8	7 5
	横方向 (A)	縦方向 (B)		4 . 0	9 8	9 4	9 0	8 6	9 7	9 3	8 9	8 6	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0
H m	1 . 2 1 H m	1 . 2 1 H m		5 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 0	8 8	8 6	8 3
				7 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 5	9 3	9 2	9 0	8 7
				1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 1	9 9	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 0

