

屋内照明器具特性	
品番 (品名)	LGBZ6116
光源	LED2700_70_3500 ×1 3500.0 lm
管理番号	K0181526 (0) DB 1
BZ分類	BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.63	0.6	56	44	37	32	54	43	36	31	50	41	35	30	46	38	33	29	26
			0.6	0.8	66	55	48	42	63	53	47	42	59	50	44	40	54	47	42	38	35
			0.56	1.0	72	62	55	50	70	61	54	49	64	57	51	47	60	54	49	45	41
				1.25	78	69	62	57	75	67	61	56	70	63	58	54	65	59	55	52	47
下方投影面積 等価発光面積		cm ²	1.5	82	74	68	63	79	72	66	61	74	68	63	59	68	64	60	56	51	
			2.0	87	81	75	71	84	78	73	69	79	74	70	66	73	69	66	63	57	
取付 高さ	器具間隔最大限		2.5	91	85	80	76	88	82	78	74	82	78	74	71	76	73	70	67	62	
	横方向 (A)	縦方向 (B)	3.0	93	88	84	80	90	85	82	78	84	80	77	74	78	76	73	71	65	
H _m	1.27H _m	1.27H _m	4.0	96	92	89	85	93	89	86	83	87	84	81	79	81	79	77	75	68	
			5.0	97	94	91	89	94	92	89	87	88	86	84	82	83	81	79	78	71	
			7.0	99	97	95	93	96	94	92	90	90	89	87	86	85	83	82	81	74	
			10.0	101	99	98	96	98	96	95	93	92	91	89	88	86	85	84	83	76	

