

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 4
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 8 7 2 0 (0) D R 1
B Z 分類	B Z 4 / 8 . 5 / B Z 5

器具効率		9 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		8 5 %																				
保守率		良 中 否	0 . 6 7	0 . 6	5 5	4 5	3 8	3 3	5 4	4 4	3 7	3 2	5 1	4 2	3 6	3 2	4 8	4 0	3 5	3 1	2 9	
			0 . 6 3	0 . 8	6 5	5 5	4 8	4 3	6 3	5 4	4 7	4 2	5 9	5 1	4 6	4 1	5 6	4 9	4 4	4 0	3 8	
			0 . 5 6	1 . 0	7 1	6 2	5 5	5 0	6 9	6 0	5 4	5 0	6 5	5 8	5 2	4 8	6 1	5 5	5 1	4 7	4 4	
				1 . 2 5	7 7	6 8	6 2	5 7	7 4	6 7	6 1	5 6	7 0	6 4	5 9	5 5	6 6	6 1	5 7	5 3	5 0	
下方投影面積		c m ²	1 . 5	8 0	7 3	6 7	6 2	7 8	7 1	6 5	6 1	7 4	6 8	6 3	5 9	7 0	6 5	6 1	5 8	5 4		
等価発光面積			c m ²	2 . 0	8 5	7 9	7 3	6 9	8 3	7 7	7 2	6 8	7 8	7 3	6 9	6 6	7 4	7 0	6 7	6 4	6 0	
取付 高さ	器具間隔最大限		2 . 5	8 8	8 3	7 8	7 4	8 6	8 1	7 6	7 3	8 1	7 7	7 3	7 0	7 7	7 3	7 1	6 8	6 4		
	横方向 (A) 縦方向 (B)		3 . 0	9 0	8 5	8 1	7 8	8 8	8 3	7 9	7 6	8 3	7 9	7 6	7 4	7 9	7 6	7 3	7 1	6 6		
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	9 3	8 9	8 5	8 2	9 0	8 7	8 4	8 1	8 6	8 3	8 0	7 8	8 1	7 9	7 7	7 5	7 0		
			5 . 0	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 7	8 5	8 3	8 1	8 3	8 1	7 9	7 8	7 3		
			7 . 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 9	8 7	8 6	8 4	8 5	8 3	8 2	8 1	7 5		
			1 0 . 0	9 7	9 6	9 4	9 2	9 5	9 4	9 2	9 0	9 1	8 9	8 8	8 7	8 6	8 5	8 4	8 3	7 8		

