

屋内照明器具特性	
品番 (品名)	LGS9302
光源	LLD40402CQ1 (SHUKOU) ×2 620.0 l m
管理番号	K0184333 (0) DR 1
BZ分類	BZ1

器具効率		9 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %						
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %						
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %						
上方光束		3 %	室指数	照明率 (X 0 . 0 1)																				Z C M			
下方光束		8 9 %																									
保守率		良 中 否	0 . 6	7 0	6 3	5 8	5 5	6 9	6 2	5 8	5 5	6 7	6 1	5 8	5 5	6 6	6 1	5 7	5 4	5 3							
			0 . 8	7 7	7 1	6 6	6 3	7 6	7 0	6 6	6 3	7 4	6 9	6 5	6 2	7 2	6 8	6 4	6 2	6 0							
			1 . 0	8 1	7 5	7 1	6 8	8 0	7 5	7 1	6 8	7 8	7 3	7 0	6 7	7 6	7 2	6 9	6 7	6 5							
			0 . 5 6	1 . 2 5	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 3	8 1	7 7	7 4	7 2	7 9	7 6	7 3	7 1	6 9						
下方投影面積		c m ²	1 . 5	8 7	8 3	7 9	7 6	8 6	8 2	7 8	7 6	8 3	8 0	7 7	7 5	8 1	7 8	7 6	7 4	7 2							
			2 . 0	9 0	8 6	8 3	8 1	8 9	8 5	8 3	8 0	8 6	8 3	8 1	7 9	8 4	8 2	8 0	7 8	7 6							
等価発光面積	c m ²	2 . 5	9 2	8 9	8 6	8 4	9 0	8 8	8 5	8 3	8 8	8 6	8 4	8 2	8 6	8 4	8 2	8 1	7 8								
		3 . 0	9 3	9 0	8 8	8 6	9 2	8 9	8 7	8 5	8 9	8 7	8 5	8 4	8 7	8 5	8 4	8 2	8 0								
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	9 4	9 2	9 0	8 9	9 3	9 1	8 9	8 8	9 0	8 9	8 7	8 6	8 8	8 7	8 6	8 5	8 2							
			5 . 0	9 5	9 4	9 2	9 1	9 4	9 2	9 1	9 0	9 1	9 0	8 9	8 8	8 9	8 8	8 7	8 6	8 3							
			7 . 0	9 6	9 5	9 4	9 3	9 5	9 4	9 3	9 2	9 2	9 1	9 0	9 0	9 0	8 9	8 8	8 8	8 5							
			1 0 . 0	9 7	9 6	9 5	9 4	9 6	9 5	9 4	9 3	9 3	9 2	9 2	9 1	9 1	9 0	8 9	8 9	8 6							