

屋内照明器具特性	
品番 (品名)	XAD1201L
光源	LED2700_70_450 ×1 450.0 lm
管理番号	K0165460 (0) DB 1
BZ分類	BZ4/0.7/BZ3

器具効率		100 % 上方光束 0 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	61	50	43	38	60	50	43	38	58	49	42	38	56	48	42	38	36
			0.63	0.8	72	62	55	50	71	61	55	50	68	60	54	50	66	59	53	49	47
			0.56	1.0	79	70	63	58	77	69	63	58	75	68	62	58	73	66	61	57	55
				1.25	85	77	71	66	83	76	70	66	81	74	69	65	78	73	68	65	63
下方投影面積 等価発光面積		cm ² cm ²	1.5	89	81	76	71	87	81	75	71	84	79	74	71	82	77	73	70	68	
			2.0	94	88	83	79	92	87	82	79	90	85	81	78	87	83	80	77	75	
			2.5	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	79	
取付 高さ	器具間隔最大限		3.0	99	94	91	88	97	93	90	87	95	91	89	86	92	90	87	85	83	
	横方向 (A)	縦方向 (B)	4.0	101	98	95	92	100	97	94	92	97	95	92	90	95	93	91	89	87	
H m	1.24 H m	1.24 H m	5.0	103	100	98	95	101	99	97	95	99	97	95	93	96	95	93	92	89	
			7.0	104	102	100	99	103	101	100	98	101	99	98	96	98	97	96	95	92	
			10.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	94	

