

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX460UENT                   |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_6680 x1 6680.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0134500(4)DB1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/2.3/BZ4                  |  |  |  |  |  |  |  |  |  |

|        |                  |         |               |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |  |  |     |
|--------|------------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|----|----|--|--|-----|
| 器具効率   | 100%             | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0% |    |  |  |     |
|        |                  | 壁       | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |  |  |     |
| 上方光束   | 0%               | 床       | 10%           |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0% |    |  |  |     |
| 下方光束   | 100%             | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |  |  | ZCM |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6           | 57  | 44  | 36  | 31  | 55  | 44  | 36  | 31  | 53  | 43 | 36 | 31  | 51 | 42 | 35 | 31 | 29 |  |  |     |
|        |                  | 0.77    | 0.8           | 67  | 55  | 47  | 42  | 65  | 55  | 47  | 42  | 63  | 53 | 46 | 41  | 60 | 52 | 46 | 41 | 39 |  |  |     |
|        |                  |         | 1.0           | 74  | 63  | 55  | 49  | 72  | 62  | 55  | 49  | 69  | 60 | 54 | 49  | 66 | 59 | 53 | 48 | 46 |  |  |     |
|        |                  | 0.68    | 1.25          | 80  | 70  | 63  | 57  | 78  | 69  | 62  | 57  | 75  | 67 | 61 | 56  | 72 | 66 | 60 | 56 | 54 |  |  |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 84            | 75  | 68  | 63  | 82  | 74  | 68  | 63  | 79  | 72  | 67 | 62 | 76  | 70 | 66 | 61 | 59 |    |  |  |     |
|        |                  | 2.0     | 90            | 82  | 76  | 72  | 88  | 81  | 76  | 71  | 85  | 79  | 74 | 70 | 82  | 77 | 73 | 70 | 67 |    |  |  |     |
| 取付高さ   | 器具間隔最大限          |         | 2.5           | 93  | 87  | 82  | 77  | 92  | 86  | 81  | 77  | 89  | 84 | 80 | 76  | 86 | 82 | 78 | 75 | 73 |  |  |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0           | 96  | 90  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87 | 83 | 80  | 89 | 85 | 82 | 79 | 76 |  |  |     |
| 1.5m   | 2.04m            | 2.15m   | 4.0           | 99  | 95  | 91  | 88  | 97  | 94  | 90  | 87  | 95  | 91 | 88 | 86  | 92 | 89 | 87 | 84 | 82 |  |  |     |
| 2      | 2.7              | 2.72    | 5.0           | 101 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94 | 91 | 89  | 94 | 92 | 90 | 88 | 85 |  |  |     |
| 2.5    | 3.37             | 3.31    | 7.0           | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96 | 95 | 93 | 92 | 89 |  |  |     |
| 3      | 4.02             | 3.91    | 10.0          | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 98  | 101 | 99 | 98 | 97  | 98 | 97 | 96 | 95 | 92 |  |  |     |

