

屋内照明器具特性

品番 (品名)	LGC35825														
光源	LED6200_70_3600 x1 3600.0 lm														
管理番号	K0157435(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%																		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																
				床	10%				10%				10%				10%				0%																
上方光束	5%	室指数																																			
下方光束	95%	照明率 (X0.01)																																			
保守率	良 中 否	0.63	0.6	0.6	0.56	ZCM																															
		0.6	0.6	0.6	0.6	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.8														
		0.6	0.6	0.6	0.6	0.6	6.6	5.4	4.7	4.1	6.4	5.4	4.6	4.1	6.1	5.2	4.5	4.0	5.8	5.0	4.4	4.0	3.7														
		0.56	0.56	0.56	0.56	0.56	7.2	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.7	5.8	5.2	4.7	6.4	5.6	5.1	4.6	4.4														
下方投影面積	c m ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0									
		等価発光面積	c m ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0		
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	
	横方向 (A)	縦方向 (B)																																			
1.5m	1.88m	1.87m	2.5	3.0	4.0	5.0	7.0	10.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0
2	2.48	2.47	2.5	3.0	4.0	5.0	7.0	10.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0
2.5	3.02	3.01	2.5	3.0	4.0	5.0	7.0	10.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0
3	3.63	3.61	2.5	3.0	4.0	5.0	7.0	10.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0	10.0	2.5	3.0	4.0	5.0	7.0	10.0

