

屋内照明器具特性	
品番 (品名)	L G C 4 1 6 0 4
光源	LED6200_70_4899 ×1 4899.0 lm
管理番号	K0164430 (0) D 1
B Z 分類	BZ6 / 1.1 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束 下方光束		9 % 9 1 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6	5 2	4 0	3 1	2 6	5 1	3 9	3 1	2 5	4 7	3 7	3 0	2 5	4 4	3 5	2 9	2 4	2 2			
			0 . 6	6 2	5 0	4 1	3 5	6 0	4 9	4 1	3 5	5 6	4 6	3 9	3 4	5 2	4 4	3 8	3 3	3 0			
			1 . 0	6 9	5 7	4 9	4 2	6 6	5 6	4 8	4 2	6 2	5 3	4 6	4 1	5 8	5 0	4 4	4 0	3 6			
			0 . 5 6	1 . 2 5	7 5	6 4	5 6	5 0	7 2	6 2	5 5	4 9	6 8	5 9	5 3	4 8	6 3	5 7	5 1	4 6	4 3		
下方投影面積		c m ²	1 . 5	7 9	6 9	6 1	5 5	7 6	6 7	6 0	5 5	7 2	6 4	5 8	5 3	6 7	6 1	5 6	5 1	4 7			
等価発光面積			c m ²	2 . 0	8 5	7 6	6 9	6 4	8 2	7 4	6 8	6 3	7 7	7 1	6 5	6 1	7 3	6 8	6 3	5 9	5 5		
取付高さ	器具間隔最大限			2 . 5	8 8	8 1	7 5	7 0	8 6	7 9	7 3	6 9	8 1	7 5	7 1	6 6	7 7	7 2	6 8	6 4	6 0		
		横方向 (A)		縦方向 (B)		3 . 0	9 1	8 5	7 9	7 4	8 8	8 3	7 7	7 3	8 4	7 9	7 4	7 1	7 9	7 5	7 1	6 8	6 4
H m		1 . 4 1 H m		1 . 4 1 H m		4 . 0	9 4	8 9	8 5	8 0	9 2	8 7	8 3	7 9	8 7	8 3	8 0	7 6	8 3	7 9	7 6	7 4	6 9
						5 . 0	9 7	9 2	8 8	8 5	9 4	9 0	8 6	8 3	8 9	8 6	8 3	8 0	8 5	8 2	8 0	7 7	7 2
						7 . 0	9 9	9 6	9 3	9 0	9 7	9 4	9 1	8 8	9 2	8 9	8 7	8 5	8 8	8 6	8 4	8 2	7 6
						1 0 . 0	1 0 1	9 9	9 6	9 4	9 9	9 6	9 4	9 2	9 4	9 2	9 0	8 9	9 0	8 8	8 7	8 5	8 0

