

屋内照明器具特性

品番 (品名)	XLX440UJNP														
光源	LED5000_85_3380 x1 3380.0 lm														
管理番号	K0144281(0)DB1														
BZ分類	BZ3														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.81	0.6	62	51	44	39	61	50	44	39	59	49	43	39	57	49	43	39	37
	中	0.77	0.8	72	62	55	50	71	61	55	50	68	60	54	50	66	59	54	50	48
	否	0.68	1.0	79	69	63	58	77	69	62	58	75	67	62	57	72	66	61	57	55
			1.25	84	76	70	65	83	75	69	65	80	74	69	64	78	72	68	64	62
下方投影面積			1.5	88	81	75	70	87	80	74	70	84	78	73	69	81	76	72	69	67
			2.0	93	87	82	78	91	86	81	77	89	84	80	77	86	82	79	76	74
取付高さ	器具間隔最大限		2.5	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	89	86	94	91	88	85	91	89	86	84	81
1.5m	1.9m	2.07m	4.0	101	97	94	91	99	96	93	91	97	94	92	89	94	92	90	88	
2	2.51	2.62	5.0	102	99	97	94	101	98	96	94	98	96	94	92	96	94	92	91	
2.5	3.13	3.19	7.0	104	102	100	98	103	101	99	97	100	99	97	96	98	96	95	94	
3	3.74	3.78	10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	94	

