

屋内照明器具特性	
品番 (品名)	XLX460SLWT
光源	LED4000_85_6080 x1 6080.0 lm
管理番号	K0144278(0)DB1
BZ分類	BZ5/0.7/BZ4/2.3/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	58	46	38	33	57	45	38	33	54	44	38	33	52	43	37	33	31
	中	0.77	0.8	68	57	49	43	66	56	49	43	64	55	48	43	61	53	47	43	41
	否	0.68	1.0	74	64	57	51	73	63	56	51	70	62	55	50	67	60	54	50	48
			1.25	80	71	64	58	79	70	63	58	76	68	62	58	73	67	61	57	55
下方投影面積			1.5	84	76	69	64	83	75	68	63	80	73	67	63	77	71	66	62	60
			2.0	90	83	77	72	88	82	76	71	85	80	75	71	82	78	73	70	67
取付高さ	器具間隔最大限		2.5	93	87	82	77	92	86	81	77	89	84	80	76	86	82	78	75	73
	横方向 (A)	縦方向 (B)	3.0	96	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76
1.5m	1.96m	2.13m	4.0	99	94	91	87	97	93	90	87	94	91	88	85	92	89	86	84	
2	2.59	2.68	5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	91	89	87	
2.5	3.23	3.25	7.0	103	100	98	95	101	99	97	94	99	97	95	93	96	94	93	91	
3	3.86	3.84	10.0	104	102	101	99	103	101	100	98	100	99	98	96	98	97	96	94	

