

屋内照明器具特性

品番 (品名)	XLX464RHWT									
光源	LED4000_85_5600 x1 5600.0lm									
管理番号	K0144274(0)DB1									
BZ分類	BZ4/0.9/BZ3/2.3/BZ4/2.8/BZ3 /3.5/BZ4/8.5/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.81	0.6	61	49	42	37	60	49	42	37	57	48	41	37	55	47	41	37	35	
	中	0.77	0.8	71	61	53	48	70	60	53	48	67	59	53	48	65	57	52	48	46	
	否	0.68	1.0	78	68	61	56	76	67	61	56	74	66	60	56	71	64	59	55	53	
			1.25	83	75	68	64	82	74	68	63	79	72	67	63	77	71	66	62	60	
下方投影面積			1.5	87	80	74	69	86	79	73	69	83	77	72	68	80	75	71	67	65	
			2.0	92	86	81	77	91	85	80	76	88	83	79	75	85	81	78	75	72	
取付高さ	器具間隔最大		2.5	95	90	86	82	94	89	85	81	91	87	84	80	89	85	82	79	77	
	横方向 (A)	縦方向 (B)	3.0	98	93	89	86	96	92	88	85	93	90	87	84	91	88	85	83	80	
1.5m	1.94m	2.07m	4.0	100	97	93	91	99	96	93	90	96	93	91	89	94	91	89	87	85	
2	2.56	2.61	5.0	102	99	96	94	101	98	95	93	98	96	94	92	96	94	92	90	88	
2.5	3.19	3.18	7.0	104	102	100	98	102	100	99	97	100	98	97	95	98	96	95	94	91	
3	3.81	3.75	10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93	

