

屋内照明器具特性

品番 (品名)	XLX455FEDT															
光源	LED6500_85_4130 x1 4130.0 1 m															
管理番号	K0132394 (2) DB 1															
BZ分類	BZ4/0.9/BZ3/1.8/BZ4															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01) ZCM																		
下方光束	100 %																				
保守率	良 中 否	0.81	0.6	61	50	42	37	60	49	42	37	57	48	42	37	55	47	41	37	35	
		0.77	0.8	71	61	54	48	70	60	53	48	67	59	53	48	65	57	52	48	46	
			1.0	77	68	61	56	76	67	61	56	73	66	60	56	71	64	59	55	53	
		0.68	1.25	83	75	68	63	82	74	68	63	79	72	67	63	76	71	66	62	60	
下方投影面積	c m ²	1.5	87	79	73	69	85	78	73	68	83	77	72	68	80	75	71	67	65		
		2.0	92	86	80	76	90	85	80	76	88	83	79	75	85	81	77	74	72		
等価発光面積	c m ²	2.5	95	90	85	81	94	89	84	81	91	87	83	80	88	85	82	79	77		
		3.0	97	93	89	85	96	91	88	84	93	89	86	83	90	87	85	82	80		
取付高さ	器具間隔最大限		4.0	100	96	93	90	98	95	92	89	96	93	90	88	93	91	89	87	84	
	横方向 (A)	縦方向 (B)	5.0	102	98	96	93	100	97	95	92	98	95	93	91	95	93	91	90	87	
1.5m	1.96 m	2.06 m	7.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	94	90		
2	2.59	2.57	10.0	105	103	102	100	103	102	101	99	101	100	99	97	99	98	97	93		
2.5	3.22	3.11																			
3	3.85	3.66																			

