

屋内照明器具特性	
品番 (品名)	L G W C 5 6 0 2 0 B F
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0125232(1)DB1
BZ分類	BZ5

器具効率	42 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	6 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	36 %																																																						
保守率	良 0.63 中 0.6 否 0.56	0.6	2.2	1.7	1.4	1.2	2.1	1.7	1.4	1.1	2.0	1.6	1.3	1.1	1.8	1.5	1.2	1.1	1.9	1.5	1.2	1.1																																	
		0.8	2.6	2.1	1.8	1.6	2.5	2.1	1.8	1.5	2.3	2.0	1.7	1.5	2.2	1.8	1.6	1.4	2.1	1.7	1.5	1.3																																	
		1.0	2.9	2.4	2.1	1.9	2.8	2.4	2.1	1.8	2.6	2.2	2.0	1.7	2.4	2.1	1.9	1.7	2.3	1.9	1.7	1.5																																	
		1.25	3.1	2.7	2.4	2.2	3.0	2.6	2.3	2.1	2.8	2.5	2.2	2.0	2.6	2.3	2.1	1.9	2.5	2.1	1.9	1.8																																	
下方投影面積	c m ²	1.5	3.3	2.9	2.6	2.4	3.2	2.8	2.6	2.3	3.0	2.7	2.4	2.2	2.7	2.5	2.3	2.1	2.7	2.5	2.3	2.1																																	
		2.0	3.6	3.2	3.0	2.7	3.4	3.1	2.9	2.7	3.2	2.9	2.7	2.5	3.0	2.8	2.6	2.4	2.9	2.7	2.6	2.2																																	
取付高さ	器具間隔最大限		2.5	3.7	3.4	3.2	3.0	3.6	3.3	3.1	2.9	3.3	3.1	2.9	2.8	3.1	2.9	2.8	2.6	2.9	2.8	2.6	2.4																																
	横方向 (A)	縦方向 (B)	3.0	3.8	3.6	3.3	3.1	3.7	3.4	3.2	3.1	3.4	3.2	3.1	2.9	3.2	3.0	2.9	2.8	2.9	2.8	2.5	2.5																																
H m	1.27 H m	1.27 H m	4.0	3.9	3.7	3.6	3.4	3.8	3.6	3.5	3.3	3.6	3.4	3.3	3.2	3.3	3.2	3.1	3.0	3.2	3.1	3.0	2.7																																
			5.0	4.0	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.7	3.5	3.4	3.3	3.4	3.3	3.2	3.1	3.3	3.2	3.1	2.9																																
			7.0	4.1	4.0	3.9	3.8	4.0	3.9	3.8	3.7	3.8	3.7	3.6	3.5	3.5	3.4	3.4	3.3	3.4	3.4	3.3	3.0																																
			10.0	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.8	3.8	3.8	3.7	3.6	3.6	3.6	3.6	3.5	3.4	3.4	3.4	3.1																																

