

屋内照明器具特性	
品番 (品名)	LGWJ 85101SU
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0128280(0)DB1
BZ分類	BZ5/0.7/BZ4

器具効率	26%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	26%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	1.5	1.2	1.0	0.9	1.5	1.2	1.0	0.9	1.4	1.2	1.0	0.9	1.4	1.1	1.0	0.9	0.8
	中	0.6	0.8	1.8	1.5	1.3	1.1	1.7	1.5	1.3	1.1	1.7	1.4	1.3	1.1	1.6	1.4	1.2	1.1	1.1
	否	0.56	1.0	2.0	1.7	1.5	1.3	1.9	1.7	1.5	1.3	1.8	1.6	1.5	1.3	1.8	1.6	1.4	1.3	1.3
			1.25	2.1	1.9	1.7	1.5	2.1	1.8	1.7	1.5	2.0	1.8	1.6	1.5	1.9	1.8	1.6	1.5	1.5
下方投影面積		cm <sup>2</sup>	1.5	2.2	2.0	1.8	1.7	2.2	2.0	1.8	1.7	2.1	1.9	1.8	1.7	2.0	1.9	1.8	1.7	1.6
等価発光面積		cm <sup>2</sup>	2.0	2.4	2.2	2.0	1.9	2.3	2.2	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	1.9	1.9	1.8
取付高さ	器具間隔最大限		2.5	2.5	2.3	2.2	2.1	2.4	2.3	2.1	2.0	2.3	2.2	2.1	2.0	2.3	2.2	2.1	2.0	1.9
	横方向 (A)	縦方向 (B)	3.0	2.5	2.4	2.3	2.2	2.5	2.4	2.2	2.2	2.4	2.3	2.2	2.1	2.3	2.2	2.2	2.1	2.0
H <sub>m</sub>	1.20H <sub>m</sub>	1.23H <sub>m</sub>	4.0	2.6	2.5	2.4	2.3	2.6	2.5	2.4	2.3	2.5	2.4	2.3	2.3	2.4	2.3	2.3	2.2	2.2
			5.0	2.6	2.6	2.5	2.4	2.6	2.5	2.5	2.4	2.5	2.5	2.4	2.3	2.5	2.4	2.4	2.3	2.2
			7.0	2.7	2.6	2.6	2.5	2.7	2.6	2.5	2.5	2.6	2.5	2.5	2.5	2.5	2.5	2.4	2.4	2.3
			10.0	2.7	2.7	2.6	2.6	2.7	2.7	2.6	2.6	2.6	2.6	2.6	2.5	2.6	2.5	2.5	2.5	2.4

