

屋内照明器具特性

品番 (品名)	S P L 5 3 4 3 K														
光源	LDA13L - G / Z100E / S / W × 3										1520.0 l m				
管理番号	K0164513 (0) DB 1														
B Z 分類	B Z 7														

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	33 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	60 %	室指数	照明率 (X0.01) Z C M																	
保守率	良	0.67	0.6	4.4	3.3	2.5	2.0	4.1	3.1	2.4	1.9	3.6	2.7	2.1	1.7	3.1	2.4	1.9	1.5	1.1
	中	0.63	0.8	5.2	4.1	3.3	2.7	4.9	3.8	3.1	2.6	4.2	3.4	2.8	2.3	3.6	2.9	2.4	2.1	1.6
	否	0.56	1.0	5.8	4.7	3.9	3.3	5.4	4.4	3.7	3.1	4.6	3.9	3.3	2.8	4.0	3.4	2.9	2.5	1.9
			1.25	6.3	5.2	4.5	3.9	5.9	4.9	4.2	3.7	5.1	4.3	3.8	3.3	4.4	3.8	3.3	2.9	2.2
下方投影面積		c m ²	1.5	6.6	5.7	4.9	4.3	6.2	5.3	4.7	4.1	5.4	4.7	4.1	3.7	4.6	4.1	3.6	3.3	2.5
等価発光面積		c m ²	2.0	7.2	6.3	5.6	5.1	6.7	6.0	5.3	4.8	5.8	5.2	4.7	4.3	5.0	4.6	4.2	3.8	3.0
取付高さ	器具間隔最大限		2.5	7.5	6.8	6.1	5.6	7.0	6.4	5.8	5.3	6.1	5.6	5.2	4.8	5.3	4.9	4.5	4.2	3.3
	横方向 (A)	縦方向 (B)	3.0	7.7	7.1	6.5	6.0	7.3	6.7	6.2	5.7	6.4	5.9	5.5	5.1	5.5	5.2	4.8	4.5	3.6
H m	1.11 H m	1.06 H m	4.0	8.1	7.5	7.0	6.6	7.6	7.1	6.7	6.3	6.7	6.3	5.9	5.6	5.8	5.5	5.2	5.0	4.0
			5.0	8.3	7.8	7.4	7.0	7.8	7.4	7.0	6.6	6.9	6.5	6.2	5.9	6.0	5.7	5.5	5.3	4.2
			7.0	8.5	8.2	7.8	7.5	8.1	7.7	7.4	7.1	7.1	6.9	6.6	6.4	6.3	6.0	5.8	5.7	4.6
			10.0	8.7	8.5	8.2	7.9	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.7	6.5	6.3	6.1	6.0	4.9

