

屋内照明器具特性

品番 (品名)	S P L 5 3 4 3 K				
光源	LDA13L - G / Z100E / S / W × 3 1520.0 l m				
管理番号	K0164513 (0) DB 1				
B Z 分類	B Z 7				

器具効率	93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		33 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
	下方光束		60 %	床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																			Z C M
保守率	良	0.67	0.6	44	33	25	20	41	31	24	19	36	27	21	17	31	24	19	15	11		
	中	0.63	0.8	52	41	33	27	49	38	31	26	42	34	28	23	36	29	24	21	16		
	否	0.56	1.0	58	47	39	33	54	44	37	31	46	39	33	28	40	34	29	25	19		
			0.56	1.25	63	52	45	39	59	49	42	37	51	43	38	33	44	38	33	29	22	
下方投影面積		c m ²	1.5	66	57	49	43	62	53	47	41	54	47	41	37	46	41	36	33	25		
等価発光面積		c m ²	2.0	72	63	56	51	67	60	53	48	58	52	47	43	50	46	42	38	30		
取付高さ	器具間隔最大限		2.5	75	68	61	56	70	64	58	53	61	56	52	48	53	49	45	42	33		
	横方向 (A)	縦方向 (B)	3.0	77	71	65	60	73	67	62	57	64	59	55	51	55	52	48	45	36		
H m	1.11 H m	1.06 H m	4.0	81	75	70	66	76	71	67	63	67	63	59	56	58	55	52	50	40		
			5.0	83	78	74	70	78	74	70	66	69	65	62	59	60	57	55	53	42		
			7.0	85	82	78	75	81	77	74	71	71	69	66	64	63	60	58	57	46		
			10.0	87	85	82	79	83	80	78	75	73	71	69	67	65	63	61	60	49		

