

屋内照明器具特性

品番 (品名)	L G W 5 1 7 0 6 W				
光源	LLD6300N ×1 1270.0 l m				
管理番号	K0165621 (0) DB 1				
B Z 分類	B Z 5				

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		3 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		73 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0.01)																				Z C M
保守率	良	0.63	0.6	4.2	3.3	2.7	2.3	4.1	3.2	2.6	2.2	3.9	3.1	2.6	2.2	3.7	3.0	2.5	2.2	2.0	
	中	0.6	0.8	4.9	4.1	3.4	3.0	4.8	4.0	3.4	3.0	4.6	3.9	3.3	2.9	4.4	3.7	3.3	2.9	2.7	
	否	0.56	1.0	5.4	4.6	4.0	3.5	5.3	4.5	3.9	3.5	5.0	4.4	3.9	3.5	4.8	4.2	3.8	3.4	3.2	
			1.25	5.9	5.1	4.5	4.1	5.7	5.0	4.5	4.1	5.5	4.9	4.4	4.0	5.2	4.7	4.3	3.9	3.7	
下方投影面積	c m ²		1.5	6.2	5.5	4.9	4.5	6.0	5.4	4.9	4.5	5.8	5.2	4.8	4.4	5.5	5.0	4.6	4.3	4.1	
	等価発光面積		c m ²	2.0	6.6	6.0	5.5	5.1	6.5	5.9	5.5	5.1	6.2	5.7	5.3	5.0	5.9	5.5	5.2	4.9	4.6
取付高さ	器具間隔最大限		2.5	6.9	6.4	5.9	5.5	6.7	6.3	5.8	5.5	6.4	6.0	5.7	5.4	6.2	5.8	5.5	5.3	5.0	
	横方向 (A)	縦方向 (B)	3.0	7.1	6.6	6.2	5.9	6.9	6.5	6.1	5.8	6.6	6.3	6.0	5.7	6.4	6.1	5.8	5.6	5.3	
H m	1.25 H m	1.25 H m	4.0	7.3	6.9	6.6	6.3	7.2	6.8	6.5	6.2	6.9	6.6	6.3	6.1	6.6	6.4	6.2	6.0	5.7	
			5.0	7.5	7.2	6.9	6.6	7.3	7.0	6.8	6.5	7.1	6.8	6.6	6.4	6.8	6.6	6.4	6.2	6.0	
			7.0	7.7	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.2	7.1	6.9	6.7	7.0	6.8	6.7	6.6	6.3	
			10.0	7.8	7.6	7.4	7.3	7.7	7.5	7.3	7.2	7.4	7.3	7.1	7.0	7.2	7.0	6.9	6.8	6.5	

