

屋内照明器具特性	
品番 (品名)	LGW51708Y
光源	LLD6300V ×1 1270.0 lm
管理番号	K0166015(0)DB1
BZ分類	BZ5

器具効率	72%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	72%	室指数	照明率 (×0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	41	32	27	23	40	32	26	23	38	31	26	23	37	30	26	22	21	
		0.8	48	40	34	30	47	39	34	30	45	38	33	30	43	37	33	30	28	
		1.0	53	45	40	35	52	45	39	35	50	43	39	35	48	42	38	35	33	
		1.25	57	50	45	41	56	49	45	41	54	48	44	40	52	47	43	40	38	
下方投影面積	c m ²	1.5	60	54	49	45	59	53	48	45	57	52	47	44	54	50	47	44	42	
		2.0	64	59	54	51	63	58	54	50	61	56	53	50	58	55	52	49	47	
取付高さ	器具間隔最大限		2.5	66	62	58	55	65	61	58	54	63	60	56	54	61	58	55	53	51
	横方向 (A)	縦方向 (B)	3.0	68	64	61	58	67	63	60	57	65	62	59	57	63	60	58	56	54
H m	1.25 H m	1.25 H m	4.0	70	67	64	62	69	66	64	61	67	65	63	61	65	63	61	60	58
			5.0	72	69	67	65	71	68	66	64	69	67	65	63	67	65	63	62	60
			7.0	73	71	70	68	72	71	69	67	70	69	67	66	69	67	66	65	63
			10.0	75	73	72	71	74	72	71	70	72	71	70	69	70	69	68	67	65

