

屋内照明器具特性	
品番 (品名)	LGB15466
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0170955(0)DR1
BZ分類	BZ5/0.9/BZ4

器具効率	60%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	60%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.4	2.7	2.2	1.9	3.3	2.6	2.2	1.8	3.2	2.6	2.1	1.8	3.0	2.5	2.1	1.8	1.7
	中	0.63	0.8	4.0	3.3	2.9	2.5	3.9	3.3	2.9	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	2.4
	否	0.56	1.0	4.5	3.8	3.4	3.0	4.4	3.8	3.4	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.3	3.0	2.9
			1.25	4.8	4.3	3.9	3.6	4.8	4.2	3.8	3.5	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	3.4
下方投影面積	c m ²		1.5	5.1	4.6	4.2	3.9	5.0	4.6	4.2	3.9	4.8	4.4	4.1	3.9	4.7	4.3	4.1	3.8	3.7
	等価発光面積		2.0	5.5	5.0	4.7	4.4	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	5.0	4.8	4.5	4.3	4.2
取付高さ	器具間隔最大限		2.5	5.7	5.3	5.0	4.8	5.6	5.3	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.8	4.7	4.5
	横方向 (A)	縦方向 (B)	3.0	5.8	5.5	5.3	5.0	5.7	5.4	5.2	5.0	5.5	5.3	5.1	4.9	5.4	5.2	5.0	4.9	4.7
H m	1.34 H m	1.34 H m	4.0	6.0	5.8	5.5	5.4	5.9	5.7	5.5	5.3	5.7	5.6	5.4	5.3	5.6	5.4	5.3	5.2	5.0
			5.0	6.1	5.9	5.7	5.6	6.0	5.8	5.7	5.5	5.8	5.7	5.6	5.4	5.7	5.6	5.5	5.4	5.2
			7.0	6.2	6.1	5.9	5.8	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.8	5.7	5.7	5.6	5.4
			10.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	6.0	6.1	6.0	5.9	5.8	5.9	5.9	5.8	5.7	5.6

