

屋内照明器具特性

品番 (品名)	XLX464FHWT									
光源	LED4000_85_4070 x1 4070.0 lm									
管理番号	K0132395(1)DB1									
BZ分類	BZ2									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81	0.6	67	58	51	47	66	57	51	47	64	56	51	47	63	55	50	47	45
		0.77	0.8	77	68	63	58	76	68	62	58	74	67	62	58	72	66	61	58	56
		0.68	1.0	83	76	70	66	82	75	70	66	80	74	69	65	78	72	68	65	63
			1.25	88	81	76	72	87	81	76	72	85	79	75	72	82	78	74	71	69
下方投影面積	c m ²	1.5	92	85	81	77	90	85	80	77	88	83	79	76	86	82	78	75	73	
		2.0	96	91	87	83	94	90	86	83	92	88	85	82	90	86	84	81	79	
取付高さ	器具間隔最大限		2.5	98	94	91	88	97	93	90	87	94	91	88	86	92	90	87	85	83
	横方向 (A)	縦方向 (B)	3.0	100	96	93	91	99	95	92	90	96	93	91	89	94	92	90	88	85
1.5m	1.79m	1.9m	4.0	102	99	97	94	101	98	96	94	98	96	94	92	96	94	93	91	89
2	2.36	2.35	5.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93	91
2.5	2.94	2.83	7.0	105	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	93
3	3.52	3.31	10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95

