

| | |
|----------|------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XLX460EENT |
| 光源 | LED5000_85_6340 x1 6340.0 lm |
| 管理番号 | K0145453 (2) DB1 |
| BZ分類 | BZ5/0.7/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 100% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.81 | 0.6 | 58 | 46 | 39 | 33 | 57 | 46 | 38 | 33 | 54 | 45 | 38 | 33 | 52 | 43 | 37 | 33 | 31 |
| | 中 | 0.77 | 0.8 | 69 | 58 | 50 | 45 | 67 | 57 | 50 | 44 | 65 | 56 | 49 | 44 | 62 | 54 | 48 | 44 | 42 |
| | 否 | 0.68 | 1.0 | 76 | 65 | 58 | 53 | 74 | 65 | 58 | 53 | 71 | 63 | 57 | 52 | 69 | 62 | 56 | 52 | 50 |
| | | | 1.25 | 82 | 73 | 66 | 60 | 80 | 72 | 65 | 60 | 77 | 70 | 64 | 60 | 74 | 68 | 63 | 59 | 57 |
| 下方投影面積 | | | 1.5 | 86 | 77 | 71 | 66 | 84 | 77 | 71 | 66 | 81 | 75 | 69 | 65 | 78 | 73 | 68 | 65 | 62 |
| | | | 2.0 | 91 | 84 | 79 | 74 | 89 | 83 | 78 | 74 | 87 | 81 | 77 | 73 | 84 | 79 | 76 | 72 | 70 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 94 | 89 | 84 | 80 | 93 | 88 | 83 | 79 | 90 | 85 | 82 | 78 | 87 | 83 | 80 | 77 | 75 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 97 | 92 | 87 | 84 | 95 | 91 | 87 | 83 | 92 | 88 | 85 | 82 | 90 | 86 | 83 | 81 | 78 |
| 1.5m | 2.04m | 2.18m | 4.0 | 99 | 96 | 92 | 89 | 98 | 94 | 91 | 88 | 95 | 92 | 90 | 87 | 93 | 90 | 88 | 86 | 83 |
| 2 | 2.69 | 2.75 | 5.0 | 101 | 98 | 95 | 92 | 100 | 97 | 94 | 92 | 97 | 95 | 92 | 90 | 95 | 92 | 91 | 89 | 86 |
| 2.5 | 3.35 | 3.35 | 7.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 99 | 97 | 96 | 94 | 97 | 95 | 94 | 92 | 90 |
| 3 | 4.01 | 3.96 | 10.0 | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99 | 101 | 100 | 98 | 97 | 98 | 97 | 96 | 95 | 92 |

