

屋内照明器具特性

品番 (品名)	XLX463EENT									
光源	LED5000_85_4880 x1					4880.0 lm				
管理番号	K0144568 (2) DB1									
BZ分類	BZ3/0.9/BZ2									

器具効率	96%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	60	50	43	38	59	49	43	38	57	48	42	38	55	47	42	38	36
	中	0.77	0.8	71	62	56	52	70	62	56	51	68	60	55	51	66	59	55	51	49
	否	0.68	1.0	78	70	64	60	77	69	64	60	75	68	63	60	72	67	63	59	58
			1.25	83	76	71	67	82	76	71	67	80	74	70	67	78	73	69	66	64
下方投影面積		cm ²	1.5	87	81	76	72	86	80	75	72	83	78	74	71	81	77	73	71	69
等価発光面積		cm ²	2.0	91	86	82	79	90	85	82	78	88	84	80	78	85	82	79	77	75
取付高さ	器具間隔最大限		2.5	94	90	86	83	92	89	85	83	90	87	84	82	88	85	83	81	79
	横方向 (A)	縦方向 (B)	3.0	95	92	89	86	94	91	88	86	92	89	87	85	90	87	85	84	81
1.5m	2.36m	2.06m	4.0	98	95	92	90	96	94	92	90	94	92	90	88	92	90	88	87	85
2	3.11	2.59	5.0	99	97	95	93	98	96	94	92	95	94	92	91	93	92	90	89	87
2.5	3.87	3.13	7.0	100	99	97	96	99	97	96	95	97	95	94	93	95	94	93	92	89
3	4.61	3.69	10.0	101	100	99	98	100	99	98	97	98	97	96	95	96	95	94	94	91

