

# 屋内照明器具特性

品番 (品名)	XLX430BSNT	
光源	LED5000_85_2900 ×1	2900.0 lm
管理番号	K0140212 (3) DR1	
BZ分類	BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 14%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束 86%			床	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																				ZCM
保守率	良 0.81	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	34	28	23	20		
	中 0.77	0.8	61	49	41	35	59	48	40	34	54	45	38	33	50	42	36	32	28		
	否 0.68	1.0	68	56	48	42	65	55	47	41	60	51	45	39	56	48	42	38	34		
		1.25	74	63	55	49	71	61	54	48	66	57	51	46	61	54	49	44	40		
下方投影面積 等価発光面積	cm <sup>2</sup>	1.5	78	68	60	54	75	66	59	53	69	62	56	51	64	58	53	49	44		
	cm <sup>2</sup>	2.0	83	75	68	62	80	73	66	61	75	68	63	58	70	64	60	56	51		
	取付高さ	器具間隔最大限		2.5	87	80	73	68	84	77	72	67	78	73	68	64	73	68	64	61	55
	横方向 (A)	縦方向 (B)	3.0	90	83	77	72	87	81	75	71	81	76	72	68	76	72	68	65	59	
1.5m	1.59m	2.11m	4.0	93	88	83	79	90	85	81	77	84	80	77	73	79	76	73	70	64	
2	2.11	2.66	5.0	95	91	86	83	92	88	84	81	86	83	80	77	81	78	76	73	67	
2.5	2.63	3.23	7.0	98	94	91	88	95	91	88	86	89	86	84	82	84	82	80	78	71	
3	3.15	3.82	10.0	100	97	94	92	97	94	92	90	91	89	87	85	86	84	83	81	75	

