

屋内照明器具特性

品番 (品名)	XLX450BSNT									
光源	LED5000_85_4650 x1 4650.0 lm									
管理番号	K0140212(3)DR1									
BZ分類	BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	14%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	86%																																																						
保守率	良 中 否	0.81	0.6	5.2	3.9	3.1	2.5	5.0	3.8	3.0	2.5	4.6	3.6	2.9	2.4	4.2	3.4	2.8	2.3	2.0																																			
		0.77	0.8	6.1	4.9	4.1	3.5	5.9	4.8	4.0	3.4	5.4	4.5	3.8	3.3	5.0	4.2	3.6	3.2	2.8																																			
		0.68	1.0	6.8	5.6	4.8	4.2	6.5	5.5	4.7	4.1	6.0	5.1	4.5	3.9	5.6	4.8	4.2	3.8	3.4																																			
			1.25	7.4	6.3	5.5	4.9	7.1	6.1	5.4	4.8	6.6	5.7	5.1	4.6	6.1	5.4	4.9	4.4	4.0																																			
下方投影面積	c m ²	1.5	7.8	6.8	6.0	5.4	7.5	6.6	5.9	5.3	6.9	6.2	5.6	5.1	6.4	5.8	5.3	4.9	4.4																																				
		2.0	8.3	7.5	6.8	6.2	8.0	7.3	6.6	6.1	7.5	6.8	6.3	5.8	7.0	6.4	6.0	5.6	5.1																																				
		2.5	8.7	8.0	7.3	6.8	8.4	7.7	7.2	6.7	7.8	7.3	6.8	6.4	7.3	6.8	6.4	6.1	5.5																																				
取付高さ	器具間隔最大限		3.0	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.1	7.6	7.2	6.8	7.6	7.2	6.8	6.5	5.9																																			
	横方向 (A)	縦方向 (B)																																																					
1.5m	1.59m	2.11m	4.0	9.3	8.8	8.3	7.9	9.0	8.5	8.1	7.7	8.4	8.0	7.7	7.3	7.9	7.6	7.3	7.0	6.4																																			
2	2.11	2.66	5.0	9.5	9.1	8.6	8.3	9.2	8.8	8.4	8.1	8.6	8.3	8.0	7.7	8.1	7.8	7.6	7.3	6.7																																			
2.5	2.63	3.23	7.0	9.8	9.4	9.1	8.8	9.5	9.1	8.8	8.6	8.9	8.6	8.4	8.2	8.4	8.2	8.0	7.8	7.1																																			
3	3.15	3.82	10.0	10.0	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.1	8.9	8.7	8.5	8.6	8.4	8.3	8.1	7.5																																			

