

屋内照明器具特性

品番 (品名)	LGB10719K									
光源	LED6200_70_462 x1					462.0 lm				
管理番号	K0153702(0)DB1									
BZ分類	BZ4/2.3/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		10%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	90%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	58	46	39	34	56	45	38	33	53	43	37	33	50	42	36	32	29
	中	0.63	0.8	68	57	50	44	66	56	49	44	62	53	47	43	58	51	46	42	39
	否	0.56	1.0	74	64	57	52	72	63	56	51	68	60	54	50	64	58	53	49	45
			1.25	79	70	64	58	77	69	63	58	73	66	60	56	69	63	58	55	51
下方投影面積			1.5	83	75	68	63	81	73	67	62	76	70	65	61	72	67	62	59	55
	等価発光面積		2.0	88	81	75	70	85	79	74	69	81	76	71	67	77	72	68	65	61
取付高さ	器具間隔最大限		2.5	91	85	80	75	89	83	78	74	84	79	75	72	79	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	91	86	81	78	86	82	78	75	82	78	75	72	68
Hm	1.32Hm	1.32Hm	4.0	96	92	88	84	94	89	86	83	89	85	82	80	84	82	79	77	72
			5.0	98	94	91	87	95	92	89	86	91	88	85	83	86	84	82	80	75
			7.0	100	97	94	92	97	95	92	90	93	91	88	87	88	87	85	83	78
			10.0	101	99	97	95	99	97	95	93	94	93	91	90	90	89	87	86	81

