

屋内照明器具特性	
品番 (品名)	LGB10728K
光源	LED6200_70_501 x1 501.0 lm
管理番号	K0153797(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	57	45	37	32	55	44	37	31	52	42	36	31	49	40	35	30	28
	中	0.63	0.8	65	54	46	40	63	53	45	40	60	51	44	39	56	49	43	38	35
	否	0.56	1.0	71	60	53	47	69	59	52	46	65	57	50	45	62	54	49	44	41
			1.25	77	67	59	54	75	65	58	53	70	63	57	52	67	60	55	50	47
下方投影面積		cm ²	1.5	81	72	65	59	79	70	63	58	74	67	61	57	70	64	59	55	51
等価発光面積		cm ²	2.0	86	79	72	67	84	77	71	66	79	73	68	64	75	70	66	62	58
取付高さ	器具間隔最大限		2.5	90	83	77	72	87	81	76	71	83	78	73	69	79	74	71	67	63
	横方向 (A)	縦方向 (B)	3.0	92	86	81	77	90	84	80	76	85	81	77	73	81	77	74	71	67
Hm	1.16Hm	1.16Hm	4.0	96	91	86	83	93	89	85	81	89	85	82	79	85	81	79	76	72
			5.0	98	93	90	86	95	91	88	85	91	88	85	82	87	84	82	79	75
			7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	85	84	79
			10.0	102	99	97	95	99	97	95	93	95	93	92	90	91	90	88	87	82

