

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX468GENT                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_6200 x1 6200.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0146093(3)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/0.7/BZ4                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |      |                  |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
|--------|------------------|---------|------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|----|----|
| 器具効率   | 100%             | 天井      | 80%  |                  |     |     | 70% |     |     |     | 50% |     |    |    | 30% |     |    |    | 0% |    |
|        |                  |         | 壁    | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0% |
| 上方光束   | 0%               | 反射率     | 床    | 10%              |     |     |     | 10% |     |     |     | 10% |    |    |     | 10% |    |    |    | 0% |
| 下方光束   | 100%             |         | 室指数  | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6  | 58               | 46  | 38  | 33  | 56  | 45  | 38  | 33  | 54  | 44 | 37 | 33  | 52  | 43 | 37 | 32 | 31 |
|        |                  | 0.77    | 0.8  | 68               | 57  | 49  | 44  | 67  | 56  | 49  | 44  | 64  | 55 | 49 | 44  | 62  | 54 | 48 | 43 | 41 |
|        |                  |         | 1.0  | 75               | 65  | 58  | 52  | 74  | 64  | 57  | 52  | 71  | 62 | 56 | 51  | 68  | 61 | 56 | 51 | 49 |
|        |                  | 0.68    | 1.25 | 81               | 72  | 65  | 60  | 80  | 71  | 65  | 60  | 77  | 69 | 64 | 59  | 74  | 68 | 63 | 59 | 56 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 85   | 77               | 71  | 65  | 84  | 76  | 70  | 65  | 81  | 74  | 69 | 65 | 78  | 72  | 68 | 64 | 62 |    |
|        |                  | 2.0     | 91   | 84               | 78  | 74  | 89  | 83  | 78  | 73  | 86  | 81  | 76 | 72 | 83  | 79  | 75 | 72 | 69 |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5  | 94               | 88  | 83  | 79  | 92  | 87  | 83  | 79  | 90  | 85 | 81 | 78  | 87  | 83 | 80 | 77 | 74 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0  | 96               | 91  | 87  | 83  | 95  | 90  | 86  | 83  | 92  | 88 | 85 | 82  | 89  | 86 | 83 | 80 | 78 |
| 1.5m   | 2.09m            | 2.16m   | 4.0  | 99               | 95  | 92  | 89  | 98  | 94  | 91  | 88  | 95  | 92 | 89 | 87  | 92  | 90 | 88 | 85 | 83 |
| 2      | 2.77             | 2.72    | 5.0  | 101              | 98  | 95  | 92  | 100 | 97  | 94  | 91  | 97  | 94 | 92 | 90  | 94  | 92 | 90 | 88 | 86 |
| 2.5    | 3.44             | 3.31    | 7.0  | 103              | 101 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 94  | 97  | 95 | 94 | 92 | 89 |
| 3      | 4.11             | 3.91    | 10.0 | 104              | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 99 | 98 | 97  | 98  | 97 | 96 | 95 | 92 |

