

屋内照明器具特性

品番 (品名)	NNY20511K										
光源	LED5000_85_16000 ×1 16000.0 1m										
管理番号	K0143898(0)DR1										
BZ分類	BZ4										

器具効率	100%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	2%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	98%																																																			
保守率	良 中 否	0.83	0.6	58	47	39	34	57	46	39	34	55	45	38	34	52	44	38	33	31																																
		0.81	0.8	69	58	50	45	67	57	50	44	64	55	49	44	62	54	48	44	42																																
		0.77	1.0	75	65	58	52	74	64	57	52	71	62	56	52	68	61	55	51	49																																
			1.25	81	72	65	60	79	71	65	60	76	69	64	59	73	67	62	58	56																																
下方投影面積	c m ²	1.5	85	77	71	66	83	76	70	65	80	74	69	64	77	72	67	64	61																																	
		2.0	91	84	78	74	89	83	77	73	86	80	76	72	83	78	74	71	68																																	
等価発光面積	c m ²	2.5	94	88	83	79	92	87	82	79	89	85	81	77	86	82	79	76	73																																	
		3.0	96	91	87	83	95	90	86	82	91	88	84	81	89	85	82	80	77																																	
取付高さ	器具間隔最大限		4.0	99	95	92	89	98	94	91	88	94	91	89	86	92	89	87	85	82																																
	横方向 (A)	縦方向 (B)	5.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	88	85																																
H m	1.25 H m	1.25 H m	7.0	103	100	98	96	101	99	97	95	98	97	95	93	96	94	93	91	88																																
			10.0	104	103	101	99	103	101	100	98	100	99	97	96	97	96	95	94	91	88																															

