

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX450BSNT                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_4650 x1 4650.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0140212(3)DR1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |             |         |      |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-------------|---------|------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%        | 天井      | 80%  |                 |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |             |         | 壁    | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 14%         | 反射率     | 床    | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 下方光束   | 86%         |         | 室指数  | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否 | 0.81    | 0.6  | 5.2             | 3.9 | 3.1 | 2.5 | 5.0 | 3.8 | 3.0 | 2.5 | 4.6 | 3.6 | 2.9 | 2.4 | 4.2 | 3.4 | 2.8 | 2.3 | 2.0 |
|        |             | 0.77    | 0.8  | 6.1             | 4.9 | 4.1 | 3.5 | 5.9 | 4.8 | 4.0 | 3.4 | 5.4 | 4.5 | 3.8 | 3.3 | 5.0 | 4.2 | 3.6 | 3.2 | 2.8 |
|        |             | 0.68    | 1.0  | 6.8             | 5.6 | 4.8 | 4.2 | 6.5 | 5.5 | 4.7 | 4.1 | 6.0 | 5.1 | 4.5 | 3.9 | 5.6 | 4.8 | 4.2 | 3.8 | 3.4 |
|        |             |         | 1.25 | 7.4             | 6.3 | 5.5 | 4.9 | 7.1 | 6.1 | 5.4 | 4.8 | 6.6 | 5.7 | 5.1 | 4.6 | 6.1 | 5.4 | 4.9 | 4.4 | 4.0 |
| 下方投影面積 |             |         | 1.5  | 7.8             | 6.8 | 6.0 | 5.4 | 7.5 | 6.6 | 5.9 | 5.3 | 6.9 | 6.2 | 5.6 | 5.1 | 6.4 | 5.8 | 5.3 | 4.9 | 4.4 |
| 等価発光面積 |             |         | 2.0  | 8.3             | 7.5 | 6.8 | 6.2 | 8.0 | 7.3 | 6.6 | 6.1 | 7.5 | 6.8 | 6.3 | 5.8 | 7.0 | 6.4 | 6.0 | 5.6 | 5.1 |
| 取付高さ   | 器具間隔最大限     |         | 2.5  | 8.7             | 8.0 | 7.3 | 6.8 | 8.4 | 7.7 | 7.2 | 6.7 | 7.8 | 7.3 | 6.8 | 6.4 | 7.3 | 6.8 | 6.4 | 6.1 | 5.5 |
|        | 横方向 (A)     | 縦方向 (B) | 3.0  | 9.0             | 8.3 | 7.7 | 7.2 | 8.7 | 8.1 | 7.5 | 7.1 | 8.1 | 7.6 | 7.2 | 6.8 | 7.6 | 7.2 | 6.8 | 6.5 | 5.9 |
| 1.5m   | 1.59m       | 2.11m   | 4.0  | 9.3             | 8.8 | 8.3 | 7.9 | 9.0 | 8.5 | 8.1 | 7.7 | 8.4 | 8.0 | 7.7 | 7.3 | 7.9 | 7.6 | 7.3 | 7.0 | 6.4 |
| 2      | 2.11        | 2.66    | 5.0  | 9.5             | 9.1 | 8.6 | 8.3 | 9.2 | 8.8 | 8.4 | 8.1 | 8.6 | 8.3 | 8.0 | 7.7 | 8.1 | 7.8 | 7.6 | 7.3 | 6.7 |
| 2.5    | 2.63        | 3.23    | 7.0  | 9.8             | 9.4 | 9.1 | 8.8 | 9.5 | 9.1 | 8.8 | 8.6 | 8.9 | 8.6 | 8.4 | 8.2 | 8.4 | 8.2 | 8.0 | 7.8 | 7.1 |
| 3      | 3.15        | 3.82    | 10.0 | 10.0            | 9.7 | 9.4 | 9.2 | 9.7 | 9.4 | 9.2 | 9.0 | 9.1 | 8.9 | 8.7 | 8.5 | 8.6 | 8.4 | 8.3 | 8.1 | 7.5 |

