

# 屋内照明器具特性

品番 (品名)	XL X4 6 0 B S W T														
光源	LED4000_85_5870 x1 5870.0 lm														
管理番号	K0140212 (3) DR 1														
BZ分類	BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	14 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	86 %	室指数	照明率 ( X0.01) ZCM																	
保守率	良 0.81 中 0.77 否 0.68	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	34	28	23	20	
		0.8	61	49	41	35	59	48	40	34	54	45	38	33	50	42	36	32	28	
		1.0	68	56	48	42	65	55	47	41	60	51	45	39	56	48	42	38	34	
		1.25	74	63	55	49	71	61	54	48	66	57	51	46	61	54	49	44	40	
下方投影面積	c m <sup>2</sup>	1.5	78	68	60	54	75	66	59	53	69	62	56	51	64	58	53	49	44	
		2.0	83	75	68	62	80	73	66	61	75	68	63	58	70	64	60	56	51	
取付高さ	器具間隔最大限		2.5	87	80	73	68	84	77	72	67	78	73	68	64	73	68	64	61	55
	横方向 (A)	縦方向 (B)	3.0	90	83	77	72	87	81	75	71	81	76	72	68	76	72	68	65	59
1.5m	1.59 m	2.11 m	4.0	93	88	83	79	90	85	81	77	84	80	77	73	79	76	73	70	64
2	2.11	2.66	5.0	95	91	86	83	92	88	84	81	86	83	80	77	81	78	76	73	67
2.5	2.63	3.23	7.0	98	94	91	88	95	91	88	86	89	86	84	82	84	82	80	78	71
3	3.15	3.82	10.0	100	97	94	92	97	94	92	90	91	89	87	85	86	84	83	81	75

