

屋内照明器具特性

品番 (品名)	XLX450ZELP														
光源	LED3000_85_6670 x1 6670.0 lm														
管理番号	K0137853(2)DB1														
BZ分類	BZ5														

器具効率	100%	反射率	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
			床	10%				10%				10%				10%				0%			
上方光束	12%	室指数	照明率 (X0.01)																			ZCM	
下方光束	88%																						
保守率	良 中 否	0.77	0.6	5.5	4.3	3.5	3.0	5.3	4.2	3.5	3.0	5.0	4.0	3.4	2.9	4.7	3.8	3.2	2.8	2.5			
		0.72	0.8	6.5	5.3	4.5	4.0	6.2	5.2	4.4	3.9	5.8	4.9	4.3	3.8	5.5	4.7	4.1	3.7	3.4			
		0.68	1.0	7.1	6.0	5.2	4.6	6.8	5.9	5.1	4.6	6.4	5.6	4.9	4.4	6.0	5.3	4.7	4.3	4.0			
			1.25	7.6	6.7	5.9	5.3	7.4	6.5	5.8	5.3	6.9	6.2	5.6	5.1	6.5	5.9	5.4	4.9	4.6			
下方投影面積		等価発光面積	c m ²																				
			c m ²																				
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
1.5m	1.88m	2.11m	4.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.7	8.4	8.0	7.7	8.3	8.0	7.7	7.4	6.9			
2	2.47	2.61	5.0	9.7	9.3	8.9	8.6	9.4	9.1	8.7	8.4	8.9	8.6	8.3	8.1	8.5	8.2	8.0	7.8	7.2			
2.5	3.07	3.15	7.0	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.2	8.9	8.7	8.5	8.7	8.5	8.3	8.2	7.6			
3	3.66	3.71	10.0	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.3	9.4	9.2	9.0	8.9	8.9	8.8	8.6	8.5	7.9			

