

屋内照明器具特性	
品番 (品名)	NNF 2 6 9 0 1 C
光源	LED3000_70_2040 ×1 2040.0 lm
管理番号	K0171121 (0) D 1
B Z 分類	BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	51	39	31	25	49	38	30	25	45	35	28	24	42	33	27	23	20
			0.67	0.8	61	48	40	34	58	47	39	33	54	44	37	32	49	41	35	31	27
			1.0	67	55	47	41	64	54	46	40	59	50	43	38	55	47	41	37	32	
			0.63	1.25	73	62	54	48	70	60	52	47	64	56	50	45	59	53	47	43	38
下方投影面積		cm ²	1.5	77	67	59	53	74	65	58	52	68	61	54	49	63	57	52	47	42	
			等価発光面積		cm ²	2.0	83	74	67	61	80	72	65	60	74	67	62	57	68	63	58
取付 高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53	
	横方向 (A) 縦方向 (B)		3.0	89	82	76	71	86	80	74	70	80	75	70	66	74	70	66	63	57	
1.5m	2.05 m	1.95 m	4.0	92	87	82	77	89	84	80	76	83	79	75	72	78	74	71	68	62	
2	2.73	2.57	5.0	94	90	85	82	91	87	83	80	85	82	79	76	80	77	74	72	65	
2.5	3.41	3.2	7.0	97	93	90	87	94	91	88	85	88	85	83	80	83	80	78	76	69	
3	4.06	3.81	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	81	80	73	

