

# 屋内照明器具特性

|         |   |  |          |  |  |
|---------|---|--|----------|--|--|
| 品番 (品名) | LGD1111N                                    |  |          |  |  |
| 光源      | LED5000_70_330 x1                           |  | 330.0 lm |  |  |
| 管理番号    | K0160146(0)DB1                              |  |          |  |  |
| BZ分類    | BZ3/1.4/BZ2/1.8/BZ3/2.3/BZ2/4.5/BZ3/6.0/BZ2 |  |          |  |  |

|        |                  |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |     |    |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|-----|----|
| 器具効率   | 100%             | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |     | 0% |     |    |
|        | 上方光束             |          | 0%               | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70 | 50  | 30 | 10  | 0% |
|        | 下方光束             |          | 100%             |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 )    |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    | ZCM |    |
| 保守率    | 良                | 0.67     | 0.6              | 63  | 53  | 46  | 41  | 62  | 52  | 45  | 41  | 60  | 51  | 45  | 41  | 58  | 50 | 45  | 41 | 39  |    |
|        | 中                | 0.63     | 0.8              | 74  | 64  | 58  | 53  | 73  | 64  | 57  | 53  | 70  | 62  | 57  | 53  | 68  | 61 | 56  | 52 | 51  |    |
|        | 否                | 0.56     | 1.0              | 81  | 72  | 66  | 61  | 79  | 71  | 66  | 61  | 77  | 70  | 65  | 61  | 75  | 69 | 64  | 60 | 59  |    |
|        |                  |          | 1.25             | 86  | 79  | 73  | 69  | 85  | 78  | 73  | 69  | 83  | 77  | 72  | 68  | 80  | 75 | 71  | 68 | 66  |    |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 90  | 83  | 78  | 74  | 89  | 83  | 78  | 74  | 86  | 81  | 77  | 73  | 84  | 79 | 76  | 73 | 71  |    |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 95  | 89  | 85  | 81  | 93  | 89  | 84  | 81  | 91  | 87  | 83  | 80  | 89 | 85  | 82 | 79  | 77 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 98  | 93  | 89  | 86  | 96  | 92  | 89  | 86  | 94  | 90  | 87  | 85  | 91  | 89 | 86  | 84 | 82  |    |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 99  | 96  | 92  | 89  | 98  | 95  | 92  | 89  | 96  | 93  | 90  | 88  | 93  | 91 | 89  | 87 | 84  |    |
| H m    | 1.18 H m         | 1.18 H m | 4.0              | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94 | 92  | 90 | 88  |    |
|        |                  |          | 5.0              | 103 | 101 | 98  | 96  | 102 | 100 | 98  | 96  | 99  | 98  | 96  | 94  | 97  | 96 | 94  | 93 | 90  |    |
|        |                  |          | 7.0              | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98 | 97  | 96 | 93  |    |
|        |                  |          | 10.0             | 106 | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99 | 98  | 98 | 95  |    |

