

屋内照明器具特性

品番 (品名)	LGC31123														
光源	LED6200_70_4100 x1 4100.0 lm														
管理番号	K0168479(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	2%	反射率	床	10%				10%				10%				10%				0%
下方光束	98%		室指数	照明率 (X0.01) ZCM																
保守率	良	0.63	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26
	中	0.6	0.8	65	53	45	39	63	52	45	39	60	51	44	39	58	49	43	38	36
	否	0.56	1.0	72	61	53	47	70	60	52	46	67	58	51	46	64	56	50	45	43
			1.25	78	68	60	54	76	67	60	54	73	65	58	53	70	63	57	53	50
下方投影面積			1.5	82	73	66	60	80	72	65	60	77	70	64	59	74	67	62	58	55
等価発光面積			2.0	88	80	74	69	86	79	73	68	83	77	72	67	79	74	70	66	63
取付高さ	器具間隔最大限		2.5	92	85	79	75	90	84	78	74	86	81	77	73	83	79	75	72	69
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	89	85	81	77	86	82	79	76	73
Hm	1.37Hm	1.37Hm	4.0	97	93	89	85	96	91	88	84	92	89	86	83	89	86	84	81	78
			5.0	99	96	92	89	98	94	91	88	95	92	89	86	92	89	87	85	81
			7.0	102	99	96	94	100	97	95	93	97	95	93	91	94	92	91	89	86
			10.0	103	101	99	98	102	100	98	96	99	97	96	94	96	95	94	92	89

