

屋内照明器具特性

品番 (品名)	LGD9102K	
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 1 m	
管理番号	K0183949 (0) DR 1	
BZ分類	BZ1	

器具効率	97%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	97%	床		10%				10%				10%				10%				0%			
室指数	照明率 (X 0.01)																			ZCM			
保守率	良 0.67	0.6	0.6	85	80	77	74	84	79	76	74	83	79	76	74	82	78	76	74	73			
	中 0.63		0.8	89	85	82	80	89	85	82	80	87	84	81	79	86	83	81	79	78			
	否 0.56		1.0	92	88	85	83	92	88	85	83	90	87	85	83	89	86	84	82	81			
下方投影面積	cm ²	等価発光面積	cm ²	1.25	95	91	89	86	94	91	88	86	92	90	87	86	91	89	87	85	84		
				1.5	96	93	91	89	96	93	90	88	94	91	89	88	92	90	88	87	86	86	
取付高さ	器具間隔最大限		Hm	0.75Hm	0.75Hm	2.5	100	97	95	94	99	97	95	93	97	95	94	92	95	94	92	91	90
	横方向 (A)	縦方向 (B)				3.0	101	99	97	95	99	98	96	95	98	96	95	94	96	95	93	92	91
Hm	0.75Hm	0.75Hm	4.0	102	100	99	97	101	99	98	97	99	97	96	95	97	96	95	94	92	91	91	91
			5.0	102	101	100	99	101	100	99	98	99	98	97	96	97	96	96	95	94	92	91	91
Hm	0.75Hm	0.75Hm	7.0	103	102	101	100	102	101	100	99	100	99	98	98	98	97	97	96	94	93	93	93
			10.0	103	103	102	101	102	102	101	101	100	100	99	99	98	98	98	97	97	96	94	93

