

# 屋内照明器具特性

品番 (品名)	XNW2 5 3 0 WV	
光源	LED3500_85_1785 ×1	1785.0 lm
管理番号	K0167852 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.83	0.6	76	69	64	60	75	68	64	60	74	67	63	60	72	67	63	60	59	
	中 0.81		0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67
	否 0.77		1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	76	74	72
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	93	87	83	80	91	86	83	80	89	85	82	79	88	84	81	79	77	
		1.5	95	90	87	84	94	90	86	83	92	88	85	83	90	87	84	82	80	
取付高さ	器具間隔最大限		2.0	98	95	91	89	97	94	91	88	95	92	90	88	93	91	89	85	
	Hm	0.71Hm	2.5	100	97	94	92	99	96	94	92	97	95	92	91	95	93	91	90	88
Hm		0.71Hm	3.0	102	99	96	94	100	98	96	94	98	96	94	93	96	94	93	92	89
	Hm	0.71Hm	4.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	92
Hm			5.0	104	102	101	99	103	101	100	99	101	99	98	97	99	98	97	96	93
	Hm		7.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95
Hm			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96	96

