

屋内照明器具特性

品番 (品名)	LGD9102K									
光源	LLD5000LCC1 ×1					1140.0 lm				
管理番号	K0188663(0)DR1									
BZ分類	BZ3/1.1/BZ2/3.5/BZ3/6.0/BZ2									

器具効率	99%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	64	54	47	43	63	53	47	42	61	52	46	42	59	51	46	42	40
	中	0.63	0.8	74	65	59	54	73	64	58	54	70	63	58	53	68	62	57	53	51
	否	0.56	1.0	81	72	66	62	79	71	66	62	77	70	65	61	74	69	64	61	59
			1.25	86	79	73	69	84	78	73	68	82	76	71	68	79	74	71	67	65
下方投影面積	cm ²		1.5	89	83	78	74	88	82	77	73	85	80	76	73	83	78	75	72	70
等価発光面積	cm ²		2.0	94	88	84	81	92	87	83	80	90	86	82	79	87	84	81	78	76
取付高さ	器具間隔最大限		2.5	96	92	88	85	95	91	87	84	92	89	86	83	90	87	85	82	80
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	88	94	91	89	86	92	89	87	85	83
Hm	1.27Hm	1.27Hm	4.0	101	98	95	93	99	96	94	92	97	94	92	90	94	92	90	89	86
			5.0	102	99	97	95	101	98	96	94	98	96	94	93	95	94	92	91	88
			7.0	103	102	100	98	102	100	99	97	99	98	97	96	97	96	95	94	91
			10.0	105	103	102	101	103	102	101	100	101	100	99	98	98	97	97	96	93

