

屋内照明器具特性

品番 (品名)	LGC58200									
光源	LED6200_70_5499 x1 5499.0 lm									
管理番号	K0181800(0)DR1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束		25%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		75%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0				
	等価発光面積		c m ²																					
取付高さ	器具間隔最大限																							
	横方向 (A)	縦方向 (B)																						
1.5m	2.01m	1.96m	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0		
2	2.64	2.57	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	
2.5	3.3	3.21	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0
3	3.92	3.82	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

