

# 屋内照明器具特性

品番 (品名)	LGC61120															
光源	LED6200_70_6099 x1 6099.0 1 m															
管理番号	K0168476 (0) DB 1															
BZ分類	BZ5															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	7 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	93 %		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否 0.63 0.6 0.56	0.6	54	42	34	28	53	41	33	28	49	39	32	27	47	38	32	27	25	
		0.8	64	52	44	38	62	51	44	38	59	49	42	37	55	47	41	36	34	
		1.0	71	60	52	46	69	58	51	45	65	56	49	44	61	54	48	43	40	
		1.25	77	67	59	53	75	65	58	53	70	63	56	51	67	60	55	50	47	
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	63	58	74	67	61	57	71	65	60	55	52	
		2.0	87	79	73	67	84	77	71	66	80	74	69	65	76	71	67	63	59	
取付高さ	器具間隔最大限		2.5	90	84	78	73	88	82	77	72	84	79	74	70	80	75	72	68	64
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	85	80	76	86	82	78	74	82	79	75	72	68
H m	1.34 H m	1.34 H m	4.0	96	91	87	83	94	90	86	82	90	86	83	80	86	83	80	77	73
			5.0	98	94	91	87	96	92	89	86	92	89	86	83	88	85	83	81	76
			7.0	100	97	95	92	98	96	93	91	94	92	90	88	90	88	87	85	80
			10.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	88	84

