

屋内照明器具特性

品番 (品名)	LGC71121														
光源	LED6200_70_8500 x1 8500.0 lm														
管理番号	K0168478(0)DB1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %														
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %														
		床	10 %				10 %				10 %				10 %				0 %														
上方光束	7 %																																
下方光束	93 %																																
室指数	照明率 (X0.01) ZCM																																
保守率	良 中 否	0.63	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	5.4	4.2	3.4	2.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.7	3.8	3.1	2.7	2.4
		0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.4	5.2	4.4	3.8	6.2	5.1	4.4	3.8	5.9	4.9	4.2	3.7	5.5	4.7	4.1	3.7	3.4			
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	7.1	6.0	5.2	4.6	6.9	5.8	5.1	4.5	6.5	5.6	5.0	4.4	6.1	5.4	4.8	4.4	4.1			
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	7.7	6.7	5.9	5.3	7.5	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.7			
下方投影面積	c m ²																																
等価発光面積	c m ²																																
取付高さ	器具間隔最大限																																
	横方向 (A)	縦方向 (B)																															
H m	1.37 H m	1.37 H m	4.0	5.0	7.0	10.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	9.0	8.7	8.3	8.0	8.6	8.3	8.1	7.8	7.4										
			5.0	7.0	10.0	9.8	9.4	9.1	8.8	9.6	9.3	8.9	8.6	9.2	8.9	8.6	8.4	8.8	8.6	8.4	8.1	7.7											
			7.0	10.0	10.1	9.8	9.5	9.3	9.9	9.6	9.3	9.1	9.5	9.2	9.0	8.8	9.1	8.9	8.7	8.6	8.1												
			10.0	10.0	10.2	10.0	9.8	9.6	1.00	9.8	9.7	9.5	9.7	9.5	9.3	9.2	9.3	9.1	9.0	8.9	8.4												

