

# 屋内照明器具特性

品番 (品名)	LGC51121														
光源	LED6200_70_5499 x1 5499.0 lm														
管理番号	K0168478(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	7%	室指数																			
下方光束	93%	照明率 (X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	ZCM																			
下方投影面積	c m <sup>2</sup>	1.25	54	42	34	28	52	41	33	28	49	39	32	27	47	38	31	27	24		
等価発光面積		c m <sup>2</sup>	1.5	64	52	44	38	62	51	44	38	59	49	42	37	55	47	41	37	34	
取付高さ	器具間隔最大限		2.5	71	60	52	46	69	58	51	45	65	56	50	44	61	54	48	44	41	
	横方向 (A)	縦方向 (B)	3.0	77	67	59	53	75	65	58	53	71	63	57	52	67	60	55	51	47	
H <sub>m</sub>	1.37H <sub>m</sub>	1.37H <sub>m</sub>	4.0	81	72	65	59	79	70	64	58	75	68	62	57	71	65	60	56	52	
			5.0	87	79	73	68	85	78	72	67	80	74	69	65	77	72	67	64	60	
			7.0	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65	
			10.0	93	87	82	78	91	86	81	77	87	82	78	75	83	79	76	73	69	
				96	92	88	84	94	90	86	83	90	87	83	80	86	83	81	78	74	
				98	94	91	88	96	93	89	86	92	89	86	84	88	86	84	81	77	
				101	98	95	93	99	96	93	91	95	92	90	88	91	89	87	86	81	
				102	100	98	96	100	98	97	95	97	95	93	92	93	91	90	89	84	

