

# 屋内照明器具特性

品番 (品名)	LGD9108	
光源	LLD2000LCS1 ×1	580.0 lm
管理番号	K0191251(1)DR1	
BZ分類	BZ1	

器具効率	33%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	33%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	2.4	2.1	2.0	1.8	2.4	2.1	2.0	1.8	2.3	2.1	1.9	1.8	2.3	2.1	1.9	1.8	1.8
	中	0.63	0.8	2.7	2.5	2.3	2.2	2.7	2.4	2.3	2.2	2.6	2.4	2.3	2.2	2.5	2.4	2.3	2.2	2.1
	否	0.56	1.0	2.9	2.7	2.5	2.4	2.8	2.6	2.5	2.4	2.8	2.6	2.5	2.4	2.7	2.6	2.5	2.4	2.3
			1.25	3.0	2.8	2.7	2.6	3.0	2.8	2.7	2.6	2.9	2.8	2.6	2.6	2.8	2.7	2.6	2.5	2.5
下方投影面積	cm <sup>2</sup>		1.5	3.1	2.9	2.8	2.7	3.1	2.9	2.8	2.7	3.0	2.9	2.8	2.7	2.9	2.8	2.7	2.7	2.6
	等価発光面積		2.0	3.2	3.1	3.0	2.9	3.2	3.0	3.0	2.9	3.1	3.0	2.9	2.8	3.0	2.9	2.9	2.8	2.8
取付高さ	器具間隔最大限		2.5	3.3	3.2	3.1	3.0	3.2	3.1	3.1	3.0	3.2	3.1	3.0	2.9	3.1	3.0	3.0	2.9	2.8
	横方向 (A)	縦方向 (B)	3.0	3.3	3.2	3.1	3.1	3.3	3.2	3.1	3.1	3.2	3.1	3.1	3.0	3.1	3.1	3.0	3.0	2.9
Hm	0.98Hm	0.98Hm	4.0	3.4	3.3	3.2	3.2	3.3	3.3	3.2	3.2	3.3	3.2	3.2	3.1	3.2	3.1	3.1	3.0	
			5.0	3.4	3.3	3.3	3.2	3.4	3.3	3.3	3.2	3.3	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.0
			7.0	3.4	3.4	3.4	3.3	3.4	3.4	3.3	3.3	3.3	3.3	3.3	3.2	3.3	3.2	3.2	3.2	3.1
			10.0	3.5	3.4	3.4	3.4	3.4	3.4	3.4	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.2	3.2	3.1

