

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGC58200                     |  |  |  |  |  |  |  |  |  |
| 光源      | LED6200_70_5499 x1 5499.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0181800(0)DR1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6/0.7/BZ5                  |  |  |  |  |  |  |  |  |  |

|        |                                    |         |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|------------------------------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%                               | 天井      | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                                    | 壁       | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 25%                                | 床       | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 75%                                | 室指数     | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.63<br>0.6<br>0.56 | 0.6     | 51            | 39 | 31 | 26 | 49  | 37 | 30 | 25 | 44  | 34 | 28 | 24 | 39  | 32 | 26 | 22 | 19  |    |
|        |                                    | 0.8     | 60            | 49 | 41 | 35 | 57  | 47 | 39 | 34 | 52  | 43 | 37 | 32 | 47  | 39 | 34 | 30 | 25  |    |
|        |                                    | 1.0     | 67            | 56 | 48 | 42 | 63  | 53 | 46 | 40 | 57  | 49 | 43 | 38 | 51  | 45 | 40 | 35 | 30  |    |
|        |                                    | 1.25    | 73            | 62 | 55 | 49 | 69  | 60 | 53 | 47 | 62  | 55 | 49 | 44 | 56  | 50 | 45 | 41 | 35  |    |
| 下方投影面積 | c m <sup>2</sup>                   | 1.5     | 77            | 67 | 60 | 54 | 73  | 64 | 58 | 52 | 66  | 59 | 54 | 49 | 60  | 54 | 49 | 46 | 39  |    |
|        |                                    | 2.0     | 82            | 74 | 68 | 62 | 78  | 71 | 65 | 60 | 71  | 65 | 60 | 56 | 64  | 60 | 56 | 52 | 45  |    |
| 取付高さ   | 器具間隔最大限                            |         | 2.5           | 86 | 79 | 73 | 68  | 82 | 76 | 70 | 66  | 74 | 69 | 65 | 61  | 68 | 64 | 60 | 57  | 49 |
|        | 横方向 (A)                            | 縦方向 (B) | 3.0           | 88 | 82 | 77 | 72  | 84 | 79 | 74 | 70  | 77 | 72 | 69 | 65  | 70 | 66 | 63 | 60  | 53 |
| 1.5m   | 2.01m                              | 1.96m   | 4.0           | 92 | 87 | 82 | 78  | 88 | 83 | 79 | 76  | 80 | 77 | 73 | 70  | 73 | 70 | 68 | 65  | 57 |
| 2      | 2.64                               | 2.57    | 5.0           | 94 | 90 | 86 | 82  | 90 | 86 | 83 | 79  | 82 | 79 | 76 | 74  | 75 | 73 | 70 | 68  | 60 |
| 2.5    | 3.3                                | 3.21    | 7.0           | 96 | 93 | 90 | 87  | 92 | 89 | 87 | 84  | 85 | 82 | 80 | 78  | 77 | 76 | 74 | 72  | 63 |
| 3      | 3.92                               | 3.82    | 10.0          | 98 | 96 | 93 | 91  | 94 | 92 | 90 | 88  | 87 | 85 | 83 | 82  | 79 | 78 | 77 | 75  | 66 |

