

屋内照明器具特性

品番 (品名)	LGC41602	
光源	LED6200_70_4550 ×1	4550.0 lm
管理番号	K0164945(0)D 1	
BZ分類	BZ6/0.7/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 16%		下方光束 84%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	53	40	32	27	51	39	32	26	47	37	30	25	43	35	29	24	21	
	中	0.6	0.8	62	50	42	36	60	49	41	36	55	46	39	34	51	43	37	33	29	
	否	0.56	1.0	68	57	49	43	66	55	48	42	61	52	46	41	56	49	43	39	35	
			1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	55	49	45	41	
下方投影面積	cm ²		1.5	78	69	62	56	75	67	60	54	70	63	57	52	65	59	54	50	45	
等価発光面積	cm ²		2.0	84	76	69	64	81	74	68	62	75	69	64	60	70	65	61	57	52	
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	78	73	68	79	73	69	65	73	69	65	62	56	
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	87	81	76	72	81	77	72	69	76	72	69	65	60	
H _m	1.30H _m	1.29H _m	4.0	93	88	84	80	90	86	82	78	85	81	77	74	79	76	73	70	64	
			5.0	95	91	87	84	92	89	85	82	87	83	80	78	81	78	76	74	67	
			7.0	98	95	92	89	95	92	89	87	89	87	84	82	84	82	80	78	71	
			10.0	100	97	95	93	97	95	93	90	91	89	88	86	86	84	83	81	74	

