

屋内照明器具特性

品番 (品名)	LGD9404														
光源	LLD5000LCC1 ×1 1140.0 lm														
管理番号	K0190413(0)DR1														
BZ分類	BZ3														

器具効率	99%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	1%	反射率	10%				10%				10%				10%				0%	
下方光束	98%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良 0.67 中 0.63 否 0.56	0.6	63	53	46	42	62	52	46	41	60	51	45	41	58	50	45	41	39	
		0.8	73	64	57	53	72	63	57	52	69	62	56	52	67	60	56	52	50	
		1.0	80	71	65	60	78	70	64	60	75	69	64	60	73	67	63	59	57	
		1.25	85	77	72	67	83	76	71	67	81	75	70	66	78	73	69	66	63	
下方投影面積	cm ²	1.5	88	82	76	72	87	81	76	72	84	79	74	71	81	77	73	70	68	
		2.0	93	87	83	79	91	86	82	78	89	84	81	77	86	82	79	76	74	
取付高さ	器具間隔最大限		2.5	96	91	87	84	94	90	86	83	91	88	85	82	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	93	90	87	96	92	89	86	93	90	87	85	91	88	86	84	81
Hm	1.26Hm	1.25Hm	4.0	100	97	94	91	98	95	93	90	96	93	91	89	93	91	89	87	85
			5.0	101	99	96	94	100	97	95	93	97	95	93	91	94	93	91	90	87
			7.0	103	101	99	97	101	100	98	96	99	97	96	94	96	95	94	93	90
			10.0	104	103	101	100	103	101	100	99	100	99	98	97	97	97	96	95	92

