

屋内照明器具特性

品番 (品名)	LGD1032L	
光源	LED2700_70_207 ×1	207.0 lm
管理番号	K0161907 (1) DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	96	93	91	89	96	93	91	89	95	92	90	89	94	92	90	89	88
	中	0.63	0.8	99	96	94	92	98	96	94	92	97	95	93	92	96	94	93	92	91
	否	0.56	1.0	101	98	96	95	100	98	96	94	99	97	95	94	98	96	95	94	93
下方投影面積 等価発光面積	cm ²	1.25	1.02	1.00	0.98	0.97	1.01	0.99	0.98	0.96	1.00	0.98	0.97	0.96	0.99	0.97	0.96	0.95	0.94	
		1.5	1.03	1.01	0.99	0.98	1.02	1.00	0.99	0.98	1.01	0.99	0.98	0.97	1.00	0.98	0.97	0.96	0.95	
		2.0	1.04	1.03	1.01	1.00	1.04	1.02	1.01	0.99	1.02	1.01	0.99	0.99	1.00	0.99	0.98	0.98	0.96	
取付高さ	器具間隔最大限		2.5	1.05	1.04	1.02	1.10	1.04	1.03	1.02	1.10	1.02	1.10	1.00	1.00	1.10	1.00	0.99	0.99	
	横方向 (A)	縦方向 (B)	3.0	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.10	1.03	1.02	1.10	1.00	1.10	1.00	1.00	0.99	
Hm	0.37Hm	0.37Hm	4.0	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.03	1.03	1.03	1.02	1.10	1.02	1.10	1.00	0.98	
			5.0	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.02	1.10	1.00	0.98	
			7.0	1.07	1.06	1.06	1.05	1.06	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.02	1.02	1.10	1.01	0.99
			10.0	1.08	1.07	1.07	1.06	1.06	1.06	1.06	1.05	1.04	1.04	1.04	1.03	1.02	1.02	1.02	1.02	0.99

